

CD52 Bandit - Full Stainless



Features & Benefits:

The CD52 family of products provide quick and easy non-intrusive pig passage detection of any pig moving between 0.01 and 20 meters per second. Non-intrusive means less maintenance and corrosion, and no possibilities of pipeline leaks.

Sensing means of the CD52-316SS consist of a set of patented, non-intrusive proprietary noise-canceling antennas invented specifically for pig passage detection. This antenna system gives the CD52-316SS its ability to reject nearby magnetic noise and halt costly false-positive triggering.

Field proven - We have been manufacturing our patented CD52 family of pig signalers for a decade. With thousands of systems installed around the globe, the CD52 family has a reliable performance record in burning deserts, frozen tundras, and every environment in between. Many of our customers are large oil and gas producers who rely upon the CD52 family of equipment to set valves, control pump stations, and communicate with SCADA systems.

Remote signaling of a passage is easy with a built-in flashing LCD visual display and dry-contact relays. These normally-open or normally-closed relays may be used in conjunction with existing SCADA systems to integrate the CD52-316SS into a pipeline control and signaling network.

Options Available:

- Sun Shade - Protection from intense sunlight.
- Heater System - Recommended for operation below -22°F (-30°C).
- Stainless Steel Tags - Tags engraved with customer information.
- Remote Indicator System (RIS) - Provides visual passage indication up to 328ft (100m).
- LineStat satellite radio for transmitting passage time, date, and GPS location via email or SMS message.



Stainless Steel Sun Shade