
## CONIC

## **DMDX**

16-48" (406-1219mm)

The Series DMDX pig come standard with the combination of two cups, two discs and brushes which provides a positive seal between dissimilar fluids and are typically used for long distance operations and light cleaning of pipelines. The increased surface area provided by multiple sealing components significantly improves overall cleaning and sealing capacity of the pig.



Size	А	В	С	Weight	Part #
16"	25.500	26.500	15.875	115	60690016
20"	31.500	32.500	20.000	187	60690020
22"	33.875	34.875	22.000	236	60690022
24"	34.875	35.875	24.000	264	60690024
30"	46.000	47.125	29.875	444	60690030
36"	53.625	55.000	36.000	653	60690036
42"	62.875	64.375	42.000	912	60690042
48"	70.500	72.125	48.000	1106	60690048

## Features:

Standard bumper noses prevent damage to both the pig and in-line auxiliary equipment. All Apache 16"-48" pigs are manufactured with by-pass ports. The ports have threaded plugs that can be removed if by-pass is required.

Designed to traverse 1.5D bends.

## Options:

- Circular flat carbon steel, stainless steel, pencil or plastic brushes.
- Transmitter housing to accommodate electronic tracking equipment.
- Aluminum or steel gauging plates are available in either slotted or standard styles.
- Magnets are available.
- Plow blades.