

Series C

GUIDE DISCS

16-48" (406-1219mm)

Apache discs can be used in both bi-directional and uni-directional applications, or in conjunction with Series C cups as sealing or guide discs. The dimensions, durometer or composition of the discs can be varied to meet any special requirements.

| Size | O.D | I.D | Weight | Part # |
|------|--------|--------|--------|------------|
| 16" | 15.250 | 8.750 | 6.0 | 91-3220-16 |
| 18" | 17.250 | 10.875 | 6.9 | 91-3220-18 |
| 20" | 19.250 | 10.875 | 11 | 91-3220-20 |
| 22" | 21.250 | 10.875 | 14 | 91-3220-22 |
| 24" | 23.250 | 14.125 | 15 | 91-3220-24 |
| 26" | 25.500 | 14.125 | 19 | 91-3220-26 |
| 28" | 27.250 | 16.125 | 25 | 91-3220-28 |
| 30" | 29.250 | 16.125 | 31 | 91-3220-30 |
| 32" | 31.250 | 20.125 | 32 | 91-3220-32 |
| 34" | 33.250 | 20.125 | 39 | 91-3220-34 |
| 36" | 35.250 | 22.125 | 45 | 91-3220-36 |
| 38" | 37.250 | 22.125 | 54 | 91-3220-38 |
| 40" | 39.250 | 22.125 | 63 | 91-3220-40 |
| 42" | 41.250 | 24.250 | 76 | 91-3220-42 |
| 48" | 47.250 | 32.125 | 97 | 91-3220-48 |



All Apache discs are manufactured from high quality polyurethane and are available with a variety of wear resistant additives. Apache has also developed a proprietary chemically-resistant urethane suited specifically for severe environments such as hydrogen sulphide gas.