pig P R OTM

Series 53

Visual/Electrical Indication Manual/Auto Reset



THE MODEL 53 IS A COMBINATION VISUAL AND ELECTRICAL IDICATOR WITH MANUAL AND AUTOMATIC RESET.

Offering both visual and electrical indicator capabilities and manual and automatic reset features, the Model 53 is the most versatile member of Apache's pigPRO[™] Series, a patented line of intrusive pig passage indicators that reliably detect the precise location of a cleaning pig as it travels within the pipeline network. When a cleaning pig passes the system's intruding plunger, it activates the plunger and triggers a visual flag indicator, signaling the pig's location.

Base Model 53 includes a thread mounting nipple, standard lower housing with fluorocarbon O-Rings, hemispherical plunger with a flag assembly and weather sealed & explosion proof limit switch. The switch employed on this model is NEMA rated, UL listed and CSA certified to suit most applications.

Options:

Flange Mount - Flange base models are manufactured to mount to existing flanged connections and are available in class 150, 300, 600 or 900 ANSI flanges. Conversions kits are also available which enable installation onto the mountings of other manufacturers.

Extension Pole:

Aluminum extensions can be attached to enable detection of the pigs passage on buried pipelines. All pressure sealing components remain below the extension module. Available in lengths 2' to 8'.



Check out apachepipe.com/animations.html for videos on pigPRO™

world class world wide