
SCRAPER CUP

DCD

16-48" (406-1219mm)

The Series DCD pig comes standard with a combination of two sealing discs and two Series C Cups, providing a positive seal between dissimilar fluids and scraping capability. The increased surface area provided by multiple sealing components significantly improves overall cleaning and sealing capacity of the pig.



| Size | А | В | С | Weight | Part # |
|------|--------|--------|--------|--------|----------|
| 16" | 23.125 | 24.125 | 16.000 | 97 | 70683016 |
| 20" | 28.875 | 29.875 | 19.875 | 159 | 70683020 |
| 22" | 31.375 | 32.375 | 21.875 | 183 | 70683022 |
| 24" | 34.500 | 35.500 | 23.875 | 234 | 70683024 |
| 30" | 42.250 | 43.375 | 29.875 | 376 | 70683030 |
| 36" | 49.875 | 51.250 | 36.000 | 583 | 70683036 |
| 42" | 57.250 | 58.750 | 42.250 | 865 | 70683042 |
| 48" | 62.750 | 64.500 | 47.750 | 1077 | 70683048 |

Features:

Configuration of the DCD pig offers a sealing arrangement suitable for separation of dissimilar fluids together with light scraping of pipeline during longer distance operations. Standard bumper noses prevent damage to both the pig and in-line auxiliary equipment. All Apache 16"-48" pigs are manufactured with by-pass ports. The ports have threaded plugs that can be removed if by-pass is required.

Designed to traverse 1.5D bends.

Options:

- Circular flat carbon steel, stainless steel, pencil or plastic brushes.
- Transmitter housing to accommodate electronic tracking equipment.
- Aluminum or steel gauging plates are available in either slotted or standard styles.
- Magnets are available.