


ALL URETHANE

VIPRS® & SUD® PIG

2-10" (51-254mm)



VIPRS® PIG



SUD® PIG

Applications:

- Terminal loading lines
- Chemical processing
- Petrochemical
- Wood pulp and paper
- Food and beverage
- Water and wastewater treatment plants
- Packaging, loading, process and product lines and piping

Technical Assistance:

- Less wasted product means reduced BOD load charges.
- Reduced power costs mean greater efficiencies of flow and pressure.
- Cleaner product because of decreased product intermix.
- Reduced overtime through more efficient, faster cleanup.

Features:

- Provides a smooth, tight squeegeeing action while traversing elbows with radius as sharp as 1.5D.
- Batching and liquid removal at pressures as low as 15 PSI.
- Accommodates variations in pipe IDs of the same nominal size.
- Available in polyurethane compounds for pipe and tubing sizes through 12". Nitrile, Viton® and other compounds available on request.
- Food grade material available.
- **Designed to traverse 1.5D bends.**

 *Apache Pipeline Products acknowledges the design contribution from Inline Services.

1575 - 90 Ave Edmonton, AB Canada T6P 0E2

Ph: 780.416.4850 | Fax: 780.416.4829 | apachepipe.com | Email: sales@apachepipe.com

5-15

world class world wide

ALL URETHANE

VIPRS® & SUD® PIG

2-10" (51-254mm)

VIPRS® PIG

Size	Pipe I.D.	Description	Seal Discs O.D.	Overall Length
2"	1.870"	For SS Tubing	1.900"	3.400"
2"	2.067"	For S/40	2.100"	3.400"
2"	2.157"	For S/10	2.200"	3.400"
2.5"	2.370"	For SS Tubing	2.400"	4.600"
2.5"	2.637"	For S/10	2.700"	4.600"
3"	2.870"	For SS Tubing	2.900"	5.500"
3"	3.068"	For S/40	3.100"	5.500"
3"	3.260"	For S/10	3.300"	5.500"
4"	3.834"	For SS Tubing	3.900"	6.380"
4"	4.026"	For S/40	4.100"	7.500"
4"	4.260"	For S/10	4.320"	7.500"
6"	5.782"	For SS Tubing	5.900"	9.500"
6"	6.357"	For S/10	6.450"	9.500"

SUD® PIG

Size	Pipe I.D.	Description	Seal Discs O.D.	Overall Length
2"	1.870"	For SS Tubing	1.900"	3.800"
2"	2.067"	For S/40	2.100"	3.800"
2"	2.157"	For S/10	2.200"	3.800"
2.5"	2.370"	For SS Tubing	2.400"	4.600"
2.5"	2.469"	For S/40	2.500"	4.600"
2.5"	2.637"	For S/10	2.700"	4.600"
3"	2.870"	For SS Tubing	2.900"	5.500"
3"	3.068"	For S/40	3.150"	5.500"
3"	3.260"	For S/10	3.300"	5.500"
4"	3.834"	For SS Tubing	3.900"	7.750"
4"	4.026"	For S/40	4.150"	7.750"
4"	4.260"	For S/10	4.300"	7.750"
4"	4.334"	For S/5	4.460"	7.750"
6"	5.782"	For Tubing	5.900"	10.760"
6"	6.065"	For S/40	6.200"	10.760"
6"	6.357"	For S/10	6.400"	10.760"
8"	7.981"	For S/40	8.150"	
8"	8.329"	For S/10	8.250"	
8"		For S/5	8.625"	
10"		For S/5 or Sch 10	10.530"	