

UT MANDREL

6-12" (152-305mm)

The UT mandrel is very useful. Although it's primary design feature is to house a transmitter located in the center of the slotted universal mandrel, it can also accommodate virtually any configuration of cup, disc and brush. This also allows the pig to clean and batch many dissimilar fluids.



UT-UC2

Size	Sealing Surface	Length	Width	Weight	Part #
6"	9.67"	11.44"	6.375"	10	70-3812-06
8"	12.06"	14.03"	8.500"	18	70-3812-08
10"	13.79"	16.03"	10.625"	32	70-3812-10
12"	17.02"	19.62"	12.750"	49	70-3812-12

UT-UC3

Size	Sealing Surface	Length	Width	Weight	Part #
6"	10.20"	11.97"	6.375"	10.8	70-3813-06
8"	12.72"	14.69"	8.500"	19	70-3813-08
10"	14.54"	16.79"	10.625"	36	70-3813-10
12"	17.88"	20.44"	12.750"	54	70-3813-12

Features & Benefits:

- Every Series UT-UC pig is equipped with Apache Series UT-C cups. As with all Apache products, the Series UT-C cup was specifically developed to perform, efficiently and reliably. To enhance durability, it's made from Reliathane, Apache's special blend of wear-resistant polyurethane.
- The large wearing surface of the cup promotes longer life, while product pressure holds the cutting edge firmly against the pipe wall.
- Standard bumper noses cushion the pig and help to protect in-line auxiliary equipment, preventing damage.
- Every series UT pig features a transmitter cavity in the middle of the mandrel to accommodate electronic pig tracking equipment

Designed to negotiate 1.5D bends, the Series UT-UC2 and UT-UC3 pigs move reliably through piping systems.

Options Available:

- Circular flange brushes in the following types and trim materials:
 1. Trim types – flat wire or pencil.
 2. Trim material – carbon steel, stainless steel or plastic.
- CARVER discs.
- Aluminum gauge plates in slotted or standard styles.
- Magnets can be used to either collect ferrous and other construction debris, or they can be used to provide a change in magnetic field required by non-intrusive pig signaler detection devices.

